

## LAMINATED DOOR PANEL

The following is a list of the main characteristics of the product components and the materials used in their manufacture.

INFORMATION TO THE USER	We recommend careful reading of this information sheet, which fulfils all legal requirements relating to product information in their entirety and serves as a valuable aid to the correct use of the product.
TERMS OF USE	<ul style="list-style-type: none"> <li>• Installation must only be carried out by qualified and trained personnel.</li> <li>• The door panel is suitable for installation in normal indoor and domestic spaces (properly ventilated and with low atmospheric humidity).</li> <li>• The door panel must be installed in areas that are not subject to stagnation of liquids or moisture of any kind on the floor or walls.</li> </ul>
NOMINAL PASSAGE DIMENSIONS	Width: 600÷1000 mm - Height: 2000÷2100 mm (measurements refer to the pocket door system in which the panel is installed)
DOOR PANEL DIMENSIONS	Width: 625÷1025 mm - Height: 2010÷2110 mm (for more dimensions see catalogue)
DOOR LEAF	Door panel with CPL laminate coating. Hollow-core door with double solid fir wood perimeter frame (32x37+32x37 mm perimeter section) and honeycomb filler with 20 mm cells. 4 mm thick MDF covers glued with hotmelt acetovinyl glue.
AVAILABLE FINISHES	<ul style="list-style-type: none"> <li>• Matt white</li> <li>• Oak</li> <li>• Natural walnut</li> </ul>
COMPLIANCE	Complies with the Decree of 10 October 2008 (Official Gazette General Series no. 288 of 10 December 2008) on the obligation to comply with the limit set for formaldehyde emissions.
CLEANING	Regular cleaning of the door is the best way to maintain the quality of the product and its aesthetic value over time. <b>Use</b> a soft cloth dampened with water. <b>Never use</b> chemical solvents or abrasive or alkaline detergents. If it is necessary to sanitise the door panel, use a soft cloth dampened with 75% hydro-alcoholic solution.
MAINTENANCE	ORDINARY: no repairs are intended, only regularly performed inspections such as <ul style="list-style-type: none"> <li>• checking the correct closing of the door;</li> <li>• checking the condition of the gaskets (and brushes in pocket doors);</li> <li>• lubricating the hardware;</li> <li>• checking the setting of the handles.</li> </ul> EXTRAORDINARY: work in this category must be entrusted exclusively to qualified personnel.
PRECAUTIONS FOR USE	Avoid improper and inappropriate use of the product. <ul style="list-style-type: none"> <li>• Do not hang or attach loads to the door panel.</li> <li>• To avoid deformations, the door panel must not be exposed to strong thermal variations (direct exposure to radiators, heaters, etc.) and hygrometric variations (rooms with high humidity).</li> <li>• In all cases where doors are not immediately installed, they must be stored in a dry room and placed on a horizontal plane.</li> <li>• No adhesive tape of any kind should be used when installing door jambs and architraves, as the adhesives may react with the surface of the product.</li> </ul>
DISPOSAL	Once the product has been disposed of or is no longer used, all components and accessories should not be dispersed in the environment, but should be taken to the local public or private waste disposal facility, in accordance with the regulations in force.