

PRODUCT DATA SHEET: SEMI-FINISHED RAW TANGANYIKA WALNUT SLIDING DOOR PANEL

PRODUCT FEATURES

The following is a list of the most important features of the product components and the materials used in their manufacture. With regard to anything that is not stated explicitly in this Product Data Sheet, the reader is referred to the provisions of the Consumer Code, Decree-Law No. 206 of 6 September 2005, "Consumer Code, as implemented in Article 7 of Law No. 229 of 29 July 2003"

INFORMATION TO THE USER	We recommend careful reading of this information sheet, which fulfils all legal requirements relating to product information in their entirety and serves as a valuable aid to the correct use of the product.
CONDITIONS OF USE	<ul style="list-style-type: none">Installation must only be carried out by qualified and trained technicians.Suitable for installation in normal indoor and domestic spaces (properly ventilated and with low atmospheric humidity).The door must be installed in areas that are not susceptible to collecting moisture of any kind, either on the floor or on the walls.
NOMINAL PASSAGE SIZE	Width 600 ÷ 1200 mm Height 2000 ÷ 2600 mm (for further dimensions see catalogue)
DOOR PANEL SIZE	Width 635 ÷ 1235 mm Height 2010 ÷ 2610 mm (for further dimensions see catalogue)
DOOR PANEL	Honeycomb-core door composed of a fir solid wood perimeter frame (thickness: 32x37 + 32x37 mm), with 8 solid wood elements in the upper section. Honeycomb core with 20 mm cells, 4 mm thick Tanganika melamine covering layers, glued with PVA adhesives by hotmelt bonding. Door panel with raw Tanganyika walnut edging glued with hotmelt adhesive. The door is then processed further until it reaches a final thickness of 40 mm.
FINISHING	<p>Tips for obtaining a professional finish</p> <ul style="list-style-type: none">If a different shade is desired, coat the wood veneer with aniline dyes, stains and impregnating agents, wood finishes etc. This will lend the wood a more natural coloration, the coating agent is easier to apply and can always be repeated, as the wood pores never close and remain "receptive" (in short, the paint can be darkened or the shade changed by applying an additional coat).Apply an undercoat/primer layer to protect the wood.Sand wood down with fine grain sandpaper.Coat surfaces with a top paint which is compatible with the wood preservative. <p>Notes</p> <ul style="list-style-type: none">It is not advisable to use water-based paints. ECLISSE shall not be held liable for damage caused by the use of such products.Carefully follow all instructions in the data sheets for the products used.The dosages of the products applied to the door panel must always be composed in the correct quantity and viscosity. If quantities are exceeded or the mixture is diluted excessively, the adhesives and the wood layers may be softened, leading to the formation of bubbles and deformations.It is essential to apply the coat (e.g., paints or glazes) to both surfaces of the door panel in the same way.
CONFORMANCE	Conforms to the provisions of the Italian Law-Decree of 10 October 2008 regarding observation of the limit value of formaldehyde emissions, Official Gazette No. 288 of 10 December 2008.
CLEANING	Regular cleaning of the door is the best way to maintain the quality of the product and its aesthetic value over time. Use a soft cloth moistened with water. Never use chemical solvents, abrasive or alkaline cleaners. If the door panel has to be disinfected, use a soft cloth moistened with a 75% solution of alcohol in water.
MAINTENANCE	<p>REGULAR MAINTENANCE: no repairs are intended, only regularly performed inspections such as</p> <ul style="list-style-type: none">confirming that the door panel closes correctlychecking the condition of the seal (and of the brushes on sliding doors)lubricating the hardwarechecking handle settings. <p>EXCEPTIONAL MAINTENANCE: work in this category must be entrusted to qualified personnel only.</p>
PRECAUTIONS FOR USE	Improper use or misuse of the product should be avoided. Do not use any adhesive tape when fitting jambs and architraves, because the glues they contain may react with the surface of the product.
SAFETY INSTRUCTIONS FOR USE	<ul style="list-style-type: none">Do not hang on the door. Do not suspend any additional weight from the door panel.To avoid deformation the door panel must not be exposed to large temperature fluctuations (direct exposure to radiators, heaters, etc.) or changes in humidity (extremely damp atmospheres).
DISPOSAL	Once the product has been disposed of or is no longer used, all components and accessories should not be dispersed in the environment, but should be taken to the local public or private waste disposal facility, in accordance with the regulations in force.