

DOOR PANEL WITH WOOD VENEER (ECLISSE Syntesis and ECLISSE 40)

The following is a list of the main characteristics of the product components and the materials used in their manufacture.

INFORMATION TO THE USER	We recommend careful reading of this information sheet, which fulfils all legal requirements relating to product information in their entirety and serves as a valuable aid to the correct use of the product.	
TERMS OF USE	• Installation must only be carried out by qualified and trained personnel. • The door panel is suitable for installation in normal indoor and domestic spaces (properly ventilated and with low atmospheric humidity). • The door panel must be installed in areas that are not subject to stagnation of liquids or moisture of any kind on the floor or walls.	
NOMINAL PASSAGE DIMENSIONS	Width: 600÷1000 mm - Height: 2000÷3000 mm (measurements refer to the pocket or hinged door system in which the panel is installed)	
DOOR PANEL DIMENSIONS	SLIDING DOOR Width: 625÷1025 mm Height: 1992÷2992 mm (for more dimensions see catalogue)	HINGED DOOR Width: 616÷1016 mm Height: 2004÷3004 mm (for more dimensions see catalogue)
	Door panels higher than 2000 mm are fitted as standard with an adjustable internal tensioning rod that keeps the door panel in constant tension, ensuring perfect flatness with the wall. Hinged door panels higher than 2700 mm are equipped with 4 hinges as standard.	
DOOR LEAF	SLIDING DOOR Panel with wood veneer. Hollow-core door with double solid fir wood perimeter frame (30×37+30×37 mm perimeter section) and honeycomb filler with 20 mm cells. 5 mm thick MDF covers glued with hotmelt acetovinyl glue. Supplied as standard with Security Profile.	HINGED DOOR Panel with wood veneer. Hollow-core door with double solid fir wood perimeter frame (35×37+35×37 mm perimeter section) and honeycomb filler with 20 mm cells. 5 mm thick MDF covers glued with hotmelt acetovinyl glue.
AVAILABLE FINISHES	• Natural oak • Natural ash • White ash • Open pore lacquered white ash Caution. The wood veining runs HORIZONTALLY.	
COMPLIANCE	Complies with the Decree of 10 October 2008 (Official Gazette General Series no. 288 of 10 December 2008) on the obligation to comply with the limit set for formaldehyde emissions.	
CLEANING	Regular cleaning of the door is the best way to maintain the quality of the product and its aesthetic value over time. Use a soft cloth dampened with water. Never use chemical solvents or abrasive or alkaline detergents. If it is necessary to sanitise the door panel, use a soft cloth dampened with 75% hydro-alcoholic solution.	
MAINTENANCE	ORDINARY: no repairs are intended, only regularly performed inspections such as • checking the correct closing of the door; • checking the condition of the gaskets (and brushes in pocket doors); • lubricating the hardware; • checking the setting of the handles. EXTRAORDINARY: work in this category must be entrusted exclusively to qualified personnel.	
PRECAUTIONS FOR USE	Avoid improper and inappropriate use of the product. • Do not hang or attach loads to the door panel. • To avoid deformations, the door panel must not be exposed to strong thermal variations (direct exposure to radiators, heaters, etc.) and hygrometric variations (rooms with high humidity). • In all cases where doors are not immediately installed, they must be stored in a dry room and placed on a horizontal plane.	
DISPOSAL	Once the product has been disposed of or is no longer used, all components and accessories should not be dispersed in the environment, but should be taken to the local public or private waste disposal facility, in accordance with the regulations in force.	