

## GLASS AND ALUMINIUM DOOR PANEL (ECLISSE Syntesis and ECLISSE 40)

The following is a list of the main characteristics of the product components and the materials used in their manufacture.

<b>INFORMATION TO THE USER</b>	We recommend careful reading of this information sheet, which fulfils all legal requirements relating to product information in their entirety and serves as a valuable aid to the correct use of the product.	
<b>TERMS OF USE</b>	<ul style="list-style-type: none"> <li>• Installation must only be carried out by qualified and trained personnel.</li> <li>• The door panel is suitable for installation in normal indoor and domestic spaces (properly ventilated and with low atmospheric humidity).</li> <li>• The door panel must be installed in areas that are not subject to stagnation of liquids or moisture of any kind on the floor or walls.</li> </ul>	
<b>NOMINAL PASSAGE DIMENSIONS</b>	Width: 600÷1000 mm - Height: 2000÷2700 mm (measurements refer to the pocket or hinged door system in which the panel is installed)	
<b>DOOR PANEL DIMENSIONS</b>	<b>SLIDING DOOR</b> Width: 610÷1010 mm Height: 1992÷2692 mm (for more dimensions see catalogue)	<b>HINGED DOOR</b> Width: 615÷1015 mm Height: 2000÷2700 mm (for more dimensions see catalogue)
<b>DOOR LEAF</b>	<ul style="list-style-type: none"> <li>• <b>Door panel</b> with single or double toughened glass pane and painted aluminium frame.</li> <li>• <b>Lock and handle:</b> see 'Handles' section of the catalogue.</li> <li>• <b>Concealed hinges</b> adjustable on three axes (for hinged door only).</li> </ul>	
<b>AVAILABLE FINISHES</b>	<b>ALUMINIUM FRAME</b> <ul style="list-style-type: none"> <li>• Champagne</li> <li>• Bronze</li> <li>• Tobacco</li> <li>• White RAL 9010</li> </ul>	<b>GLASS PANE/PANES</b> <ul style="list-style-type: none"> <li>• Transparent extra clear (only for single-glazed sliding door)</li> <li>• Satin extra clear</li> <li>• Smoked</li> <li>• Sandblasted smoked</li> <li>• Reflex smoked</li> <li>• Bronze</li> <li>• Satin bronze</li> <li>• Reflex bronze</li> <li>• Mirror</li> </ul>
	See catalogue for further specifications	
<b>COMPLIANCE</b>	Compliant with reference standards: <ul style="list-style-type: none"> <li>• UNI 7697 - Safety criteria in glass applications;</li> <li>• UNI EN 12150 - Glass in building - Thermally toughened soda lime silicate safety glass;</li> <li>• UNI EN 12600 - Glass in building - Pendulum test - Impact test method and classification for flat glass.</li> </ul>	
<b>CLEANING</b>	Regular cleaning of the door is the best way to maintain the quality of the product and its aesthetic value over time. <b>Use</b> a soft cloth dampened with water. <b>Never use</b> products containing chlorine, bleach, caustic soda or other aggressive products. Should the material come into contact with such products, rinse immediately with water and then dry thoroughly. <b>Never use</b> abrasive products or sponges. If it is necessary to sanitise the door panel, use a soft cloth dampened with 75% hydro-alcoholic solution.	
<b>MAINTENANCE</b>	ORDINARY: no repairs are intended, only regularly performed inspections such as <ul style="list-style-type: none"> <li>• checking the correct closing of the door;</li> <li>• checking the condition of the gaskets (and brushes in pocket doors);</li> <li>• lubricating the hardware;</li> <li>• checking the setting of the handles.</li> </ul> EXTRAORDINARY: work in this category must be entrusted exclusively to qualified personnel.	
<b>PRECAUTIONS FOR USE</b>	Avoid improper and inappropriate use of the product. <ul style="list-style-type: none"> <li>• Do not hang or attach loads to the door panel.</li> </ul>	
<b>DISPOSAL</b>	Once the product has been disposed of or is no longer used, all components and accessories should not be dispersed in the environment, but should be taken to the local public or private waste disposal facility, in accordance with the regulations in force.	