

FRAMELESS GLASS SLIDING DOOR PANEL (ECLISSE Syntesis)

The following is a list of the main characteristics of the product components and the materials used in their manufacture.

INFORMATION TO THE USER	We recommend careful reading of this information sheet, which fulfils all legal requirements relating to product information in their entirety and serves as a valuable aid to the correct use of the product.	
TERMS OF USE	<ul style="list-style-type: none"> • Installation must only be carried out by qualified and trained personnel. • The door panel is suitable for installation in normal indoor and domestic spaces. 	
NOMINAL PASSAGE DIMENSIONS	Width: 600÷1000 mm - Height: 2000÷2700 mm (measurements refer to the pocket door system in which the panel is installed)	
DOOR PANEL DIMENSIONS	Width: 635÷1235 mm - Height: 1992÷2692 mm (for more dimensions see catalogue)	
DOOR LEAF	<p>Door panel: 10 mm thick tempered glass door supplied as standard with an anodised aluminium horizontal profile for support and hooking to the track.</p> <p>Handles and Locks: please refer to the catalogue for the complete and up-to-date offer.</p>	
AVAILABLE FINISHES	<p>PLAIN FINISHES</p> <ul style="list-style-type: none"> • Transparent • Transparent extra clear • Satin • Satin extra clear • Transparent smoked • Sandblasted smoked • Coloured with satin effect (10 mm thick tempered glass with satin effect coating on one side) • Coloured with opaque effect (5+5 mm thick layered tempered glass with internal opaque coating) <p>For more information see catalogue.</p>	<p>FINISHES WITH DECORATION</p> <ul style="list-style-type: none"> • Transparent with sandblasted design • Transparent extra clear with sandblasted design • Satin with sandblasted design • Satin extra clear with sandblasted design • Transparent smoked with sandblasted design • Sandblasted smoked with transparent design <p>For more information see catalogue.</p>
COMPLIANCE	<p>Compliant with reference standards:</p> <ul style="list-style-type: none"> • UNI 7697 - Safety criteria in glass applications; • UNI EN 12150 - Glass in building - Thermally toughened soda lime silicate safety glass - Part 2: Evaluation of conformity/Product standard. 	
CLEANING	<p>Regular cleaning of the door is the best way to maintain the quality of the product and its aesthetic value over time.</p> <p>Use a soft cloth dampened with water.</p> <p>Never use chemical solvents or abrasive or alkaline detergents.</p> <p>If it is necessary to sanitise the door panel, use a soft cloth dampened with 75% hydro-alcoholic solution.</p>	
MAINTENANCE	<p>ORDINARY: no repairs are intended, only regularly performed inspections such as</p> <ul style="list-style-type: none"> • checking the correct closing of the door; • checking the condition of the gaskets (and brushes in pocket doors); • lubricating the hardware; • checking the setting of the handles. <p>EXTRAORDINARY: work in this category must be entrusted exclusively to qualified personnel.</p>	
PRECAUTIONS FOR USE	<p>Avoid improper and inappropriate use of the product.</p> <ul style="list-style-type: none"> • Do not hang or attach loads to the door panel. • Avoid subjecting the door to heavy stresses, e.g. violent impacts, especially on the edges. 	
DISPOSAL	<p>Once the product has been disposed of or is no longer used, all components and accessories should not be dispersed in the environment, but should be taken to the local public or private waste disposal facility, in accordance with the regulations in force.</p>	